

stored energy solutions for a demanding world

**NARADA**

**Model: EosG1000**

**EosG Series**

The EosG range Valve Regulated Lead Acid Battery adopt gel technology and offers outstanding performance including a 15+ years design life. The EosG series batteries have been designed for the applications of telecom, UPS, solar energy system, etc. Built to the highest standards and compliant with the latest IEC60896-21/22 standard. This range also offers 100% capacity out-of-the-box and is capable of handling deep discharges for complete peace of mind. The use of flexible connectors and the ability to be installed both horizontally and vertically allows for multiple installation possibilities.



**Specifications**

Battery Model	EosG1000			
Nominal Voltage	2V			
Capacity (25°C)	10HR(100A,1.80V)	3HR (250A, 1.80V)		1HR(550A,1.75V)
	1000AH	750AH		550AH
Dimensions	Length	Width	Height	Total Height
	186mm	229mm	555mm	566mm
Approx. Weight	62.8kg			
Internal Resistance	0.18mΩ			
Max Charge Current Allowed	250A			
Charge Voltage (25°C)	Cycle use		Float use	
	2.35V/cell		2.25V/cell	
Temperature Ranges	Operation (maximum):		-40°C to 55°C(-40°F to 131°F)	
	Operation (recommended):		15°C to 25°C(59°F to 77°F)	
	Storage:		-20°C to 40°C(-4°F to 104°F)	
Terminal	M8 Female			
Terminal Hardware Torque	15 ± 1.0Nm			
Container Material	ABS (V0 optional)			

**Constant Current Discharge Characteristics Units: Amperes (25°C, 77°F)**

End voltage per cell	5min	15min	30min	1hr	2hr	3hr	5hr	6hr	8hr	10hr	24hr	48hr	100hr
1.60V	1455.0	1224.3	994.9	655.6	403.7	296.4	192.8	166.1	130.1	106.6	49.4	26.4	14.8
1.65V	1364.4	1152.4	907.3	618.8	392.3	288.4	190.4	164.2	128.9	106.0	48.7	26.2	14.6
1.70V	1282.3	1090.5	829.7	588.0	378.8	275.5	185.7	160.2	127.1	104.4	48.5	26.0	14.4
1.75V	1209.6	1026.4	765.1	551.2	364.9	269.2	182.5	157.8	125.3	103.5	48.1	25.7	14.0
1.80V	1142.8	957.3	716.3	523.0	353.9	260.8	177.1	153.6	122.0	102.1	47.1	25.2	13.5
1.85V	981.2	814.2	629.8	465.6	319.0	241.4	167.1	146.3	118.0	97.9	45.7	24.0	13.1
1.90V	803.6	642.9	523.3	382.7	266.7	214.6	151.4	132.0	106.4	89.3	42.7	22.4	12.1

**Discharge Data with Constant Power Units: Watts per cell (25°C, 77°F)**



End voltage per cell	5min	15min	30min	1hr	2hr	3hr	4hr	5hr	6hr	8hr	10hr	24hr
1.60V	2840.5	2379.0	1894.2	1348.9	870.3	644.7	514.1	425.8	363.7	284.3	232.1	104.6
1.65V	2701.6	2283.0	1791.7	1246.4	798.4	605.0	487.6	410.9	352.1	273.7	226.5	102.7
1.70V	2597.3	2202.0	1747.0	1186.9	775.3	583.5	471.1	401.7	345.2	267.8	219.9	100.7
1.75V	2516.3	2119.2	1687.4	1140.6	747.8	562.0	461.2	391.8	337.2	257.9	216.5	99.7
1.80V	2446.8	2020.0	1627.9	1114.1	733.9	542.2	446.3	380.9	327.3	251.3	213.2	98.2
1.85V	2225.1	1839.6	1447.6	1013.3	674.4	513.4	429.1	363.0	309.9	243.0	205.0	94.2
1.90V	1963.7	1596.5	1220.9	872.8	585.2	476.1	399.5	339.2	289.6	227.3	190.1	88.3

stored energy solutions for a demanding world

**NARADA**

Model: **EosG1000**

**EosG Series**



**NARADA POWER SOURCE CO.,LTD.**  
 9F, Building A, No. 50 Zijinghua Road, Hangzhou, China  
 Tel: +86-571-28827013 Fax: +86-571-28828290  
 Website: www.naradabattery.com E-mail: intl@narada.biz

**NARADA ASIA PACIFIC PTE.LTD.**  
 65 Ubi Crescent #07-05 HOLA centre, Singapore  
 Tel: +65-6848 1191 Fax: +65-6749 3498  
 E-mail: sales@narada.com.sg

**NARADA EUROPE (UK) LIMITED**  
 Spectrum House, Dunstable Road, Redbourn,  
 St. Albans, Herts AL3 7PR  
 Tel: +44 (0)845 371 7095 Fax: +44 (0)845 612 2031  
 E-mail: sales@naradaeurope.com



EosG1000-04-N-EN (Ver.04 July 2012) Subject to revision without prior notice. E. & O.E.